

CLAIMS AMENDMENTS

Please amend Claims 1, 5, 17, and 25-27, as follows:

1. (Currently Amended) An image pickup device comprising:

a plurality of pixels each including a photoelectric conversion unit, a semiconductor area to which a signal from said photoelectric conversion unit is transferred, a transfer switch ~~adapted~~ to transfer the signal from said photoelectric conversion unit to said semiconductor area, and a read unit ~~adapted~~ to read out the signal from said semiconductor area; and

a drive circuit coupled to said pixels and ~~adapted~~ to output a first signal level at which said transfer switch is set in an OFF state, a second signal level at which said transfer switch is set in an ON state, and a third signal level between the first signal level and the second signal level,

wherein said drive circuit controls to hold the third signal level for a ~~predetermined~~ part of a time period after an end of an accumulation period of accumulating a carrier in the photoelectric conversion unit until a start of transferring the signal from the photoelectric conversion unit while said transfer switch is changing from the ON state to the OFF state.

2. (Original) A device according to Claim 1, wherein said read unit includes an amplification transistor for amplifying and outputting the signal in said semiconductor area.

3. (Previously Presented) A device according to Claim 1, wherein said photoelectric conversion unit includes an embedded photodiode.

4. (Previously Presented) A device according to Claim 1, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and
a recording circuit adapted to record the signal processed by said signal
processing circuit.

5. (Currently Amended) An image pickup device comprising:
a plurality of pixels each including a photoelectric conversion unit, a
semiconductor area to which a signal from said photoelectric conversion unit is transferred, a
transfer switch ~~adapted~~ to transfer the signal from said photoelectric conversion unit to said
semiconductor area, and a read unit ~~adapted~~ to read out the signal from said semiconductor area;
and
a drive circuit coupled to said pixels and ~~adapted~~ to output a signal for
controlling said transfer switch so that a time during which said transfer switch changes from an
ON state to an OFF state becomes longer than a time during which said transfer switch changes
from the OFF state to the ON state.

6. (Original) A device according to Claim 5, wherein said read unit includes
an amplification transistor for amplifying and outputting the signal in said semiconductor area.

7. (Original) A device according to Claim 5, wherein said photoelectric conversion unit includes an embedded photodiode.

8. (Original) A device according to Claim 5, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and
a recording circuit adapted to record the signal processed by said signal
processing circuit.

9. (Withdrawn) An image pickup device comprising:
a plurality of pixels each including a photoelectric conversion unit, a
semiconductor area to which a signal from said photoelectric conversion unit is transferred, a
transfer switch adapted to transfer the signal from said photoelectric conversion unit to said
semiconductor area, and a read unit adapted to read out the signal from said semiconductor area;
and
a drive circuit adapted to control said transfer switch,
wherein a substantial driving force of said drive circuit for changing said
transfer switch from an OFF state to an ON state is higher than a substantial driving force for
changing said transfer switch from the ON state to the OFF state.

10. (Withdrawn) A device according to Claim 9, wherein said read unit includes an amplification transistor for amplifying and outputting the signal in said semiconductor area.

11. (Withdrawn) A device according to Claim 9, wherein said photoelectric conversion unit includes an embedded photodiode.

12. (Withdrawn) A device according to Claim 9, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and
a recording circuit adapted to record the signal processed by said signal
processing circuit.

13. (Withdrawn) An image pickup device comprising:
a plurality of pixels each including a photoelectric conversion unit, a
semiconductor area to which a signal from said photoelectric conversion unit is transferred, a
transfer switch adapted to transfer the signal from said photoelectric conversion unit to said
semiconductor area, and a read unit adapted to read out the signal from said semiconductor area;
and
a drive circuit adapted to control said transfer switch,

wherein said transfer switch comprises a transistor of a first conductivity type, and said drive circuit includes at least a structure formed by connecting the transistors of the first conductivity type in series.

14. (Withdrawn) A device according to Claim 13, wherein said read unit includes an amplification transistor for amplifying and outputting the signal in said semiconductor area.

15. (Withdrawn) A device according to Claim 13, wherein said photoelectric conversion unit includes an embedded photodiode.

16. (Withdrawn) A device according to Claim 13, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and
a recording circuit adapted to record the signal processed by said signal
processing circuit.

17. (Currently Amended) An image pickup device comprising:
a plurality of pixels each including a photoelectric conversion unit, a
semiconductor area to which a signal from said photoelectric conversion unit is transferred, a
transfer switch adapted to transfer the signal from said photoelectric conversion unit to said

semiconductor area, and a read unit ~~adapted~~ to read out the signal from said semiconductor area;
and

a drive circuit coupled to said pixels and ~~adapted~~ to output a signal
adapted to control said transfer switch so that a fall speed V_{off} for changing said transfer switch
from an ON state to an OFF state has a relation $10 \text{ V}/\mu\text{sec} > V_{off}$.

18. (Original) A device according to Claim 17, wherein said read unit
includes an amplification transistor for amplifying and outputting the signal in said
semiconductor area.

19. (Original) A device according to Claim 17, wherein said photoelectric
conversion unit includes an embedded photodiode.

20. (Original) A device according to Claim 17, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and a recording circuit adapted to record the signal processed
by said signal processing circuit.

21. (Withdrawn) An image pickup device comprising:
a plurality of pixels each including a photoelectric conversion unit, a
semiconductor area to which a signal from said photoelectric conversion unit is transferred, a

transfer switch adapted to transfer the signal from said photoelectric conversion unit to said semiconductor area, and a read unit adapted to read out the signal from said semiconductor area; and

a drive circuit adapted to control said transfer switch,
wherein said drive circuit includes a constant current circuit.

22. (Withdrawn) A device according to Claim 21, wherein said read unit includes an amplification transistor for amplifying and outputting the signal in said semiconductor area.

23. (Withdrawn) A device according to Claim 21, wherein said photoelectric conversion unit includes an embedded photodiode.

24. (Withdrawn) A device according to Claim 21, further comprising
an analog/digital conversion circuit adapted to convert a signal from each
of said plurality of pixels into a digital signal,
a signal processing circuit adapted to process the signal from said
analog/digital conversion circuit, and
a recording circuit adapted to record the signal processed by said signal
processing circuit.

25. (Currently Amended) A drive method for an image pickup device including a plurality of pixels each including a photoelectric conversion unit, a semiconductor

area to which a signal from said photoelectric conversion unit is transferred, a transfer switch adapted to transfer the signal from said photoelectric conversion unit to said semiconductor area, and a read unit adapted to read out the signal from said semiconductor area, comprising:

an output step of outputting a first drive signal level at which said transfer switch is set in an OFF state, a second drive signal level at which said transfer switch is set in an ON state, and a third drive signal level between the first drive signal level and the drive signal second level,

wherein the third drive signal level is held for a predetermined time while said transfer switch is changing from the ON state to the OFF state.

26. (Currently Amended) A drive method for an image pickup device including a plurality of pixels each including a photoelectric conversion unit, a semiconductor area to which a signal from said photoelectric conversion unit is transferred, a transfer switch adapted to transfer the signal from said photoelectric conversion unit to said semiconductor area, and a read unit adapted to read out the signal from said semiconductor area, comprising:

an output step of outputting a drive signal adapted to control said transfer switch so that a time during which said transfer switch changes from an ON state to an OFF state becomes longer than a time during which said transfer switch changes from the OFF state to the ON state.

27. (Currently Amended) A drive method for an image pickup device including a plurality of pixels each including a photoelectric conversion unit, a semiconductor area to which a signal from said photoelectric conversion unit is transferred, a transfer switch

adapted to transfer the signal from said photoelectric conversion unit to said semiconductor area,
and a read unit adapted to read out the signal from said semiconductor area, comprising:

an output step of outputting a drive signal adapted to control said transfer
switch so that a fall speed V_{off} for changing said transfer switch from an ON state to an OFF
state has a relation $10 \text{ V/sec} > V_{off}$.